




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H04Q 7/38		A1	(11) International Publication Number: WO 00/18171
			(43) International Publication Date: 30 March 2000 (30.03.00)
(21) International Application Number: PCT/US99/16606 (22) International Filing Date: 22 July 1999 (22.07.99) (30) Priority Data: 09/159,711 24 September 1998 (24.09.98) US (71) Applicant: BACK, Juha [FI/FI]; Kulosaaren Puistotie 44 B 22, FIN-00570 Helsinki (FI). (71)(72) Applicants and Inventors: EINOLA, Heikki [FI/FI]; Hiihtajantie 8 A 15, FIN-00810 Helsinki (FI). HULKONEN, Tony [FI/FI]; Porvoonkatu 1 F 214, FIN-00510 Helsinki (FI). HUOTARI, Seppo [FI/FI]; Albergan Esplanadi 4 B 31, FIN-02600 Espoo (FI). LAHTINEN, Lauri [FI/FI]; Kurkijoentie 7 B, FIN-02140 Espoo (FI). LE, Khiem [US/US]; 607 St-Andrews Place, Coppell, TX 75019 (US). LINDHOLM, Heikki [FI/FI]; Perasin 3 D 2, FIN-02320 Espoo (FI). RAJANIEMI, Jaakko [FI/FI]; Karstulantie 8 B 31, FIN-00550 Helsinki (FI). TIMONEN, Juha [FI/FI]; Soivotie 7, FIN-90800 Oulu (FI). (74) Agent: LYNCH, David, W.; Altera Law Group, LLC, 10749 Bren Road East, Opus 2, Minneapolis, MN 55343 (US).		(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.	

(54) Title: MOBILITY MANAGEMENT PROCEDURE WITH INDICATOR SPECIFYING CORE NETWORK ENTITY

(57) Abstract

A method, a system, or an article of manufacture provides Mobility Management (MM), an update procedure, in a Core Network (CN) of a mobile communication system. The Mobile Station (MS) includes an indicator which defines an update type. The update type includes: all CN entities; one type of CN entity only. If the indicator has the update type of all CN entities, the MS registers all CN entities. If the indicator has the update type of one type of CN entity only, the MS registers the one type of CN entity only. The CN entities may be MSC/VLR CN entity, SGSN CN entity, or other CN entity. The method includes the MS determining to which of the CN entity to perform the update procedure; the MS updating the CN entity; the CN acknowledging the MS whether update is successful or failed; and the CN acknowledging the MS whether update of other CN entity is needed, if needed, the CN defining to which of the CN entity to perform update, and continuing the update of the defined CN entity. The MS does not have to know the services subscribed to a user, nor does the MS have to know the configuration of the CN.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

MOBILITY MANAGEMENT PROCEDURE WITH INDICATOR SPECIFYING CORE NETWORK ENTITY

BACKGROUND OF THE INVENTION

5 1. Indicator of the Invention.

This invention relates in general to a mobile cellular communication system, more particularly to a mobile cellular communication system used in 2nd and 3rd generation mobile cellular system, and more still particularly to an indicator in mobility management (MM) procedures to specify a procedure type executed in
10 Core Network (CN) entities.

2. Description of Related Art.

Cellular systems have had a direct effect on the lives of millions over the past few years. For the first time, people are able to make and receive phone calls without being tied to a specific location. Mobile phones, as part of the cellular
15 systems, have allowed people to break the tie between location and access to communication. Mobile phones have also allowed people to reach another who is in move. With the development in cellular systems, people are allowed to reach another who is mobile in anywhere at anytime.

The first generation of mobile communication systems were born in the early
20 1980s. The marriage of radio and telephone technologies gave birth to mobile phones and triggered a turning point in telecommunications. Adding radio access to a telephone network meant that for the first time in history, the concept of a telephone being at a fixed point in the network was no longer valid. The benefits of being able to make and receive telephone calls anywhere had appeal to business
25 people – the original market. In the first generation of cellular networks, analog wireless technology were used for the user connection (called the “air interface”). Every voice channel had its own narrow frequency band, using a technology called Frequency Division Multiple Access (FDMA).

However, as the demand for mobile phones grew and grew, regularly
30 exceeding forecasts, it became obvious that the available radio spectrum would not be adequate to accommodate the expected numbers of mobile phone users. The digital technology became the solution to the problem. The answer lay in new digital wireless technologies that allow larger numbers of mobile subscribers to be

supported within a given frequency allocation. Time Division Multiple Access (TDMA) technology is used in which a broader frequency channel is divided into intermittent time-slots, i.e. several calls share the same frequency channel at any one time. The digital technology also offered other important benefits. It provided better voice quality and improved security against unauthorized eavesdropping. Another technology, Code Division Multiple Access (CDMA) has also been developed subsequently to increase capacity.

The first and second generation mobile communication systems were mainly set to support voice communications, although today's mobile phones can also be used for data transfer at rates that are acceptable for relatively low-speed data applications such as sending and receiving of faxes and e-mail. However, these systems do not support high-speed data or video applications. The third generation mobile communication system is being developed to remove the bandwidth bottleneck and support a whole new range of voice, data, video, and multimedia services. For example, smart messaging is bringing Internet services to every mobile user's fingertips. As people become used to the freedom that mobile communications have provided, they will become more demanding about the information and services required to benefit their lives.

The demand by consumers all over the world for mobile communications service continues to expand at a rapid pace and will continue to do so for at least the next decade. To satisfy such demand, more and more innovative mobile telecommunications networks are being built in this growing industry.

In the 3rd generation cellular systems, many practical techniques are being developed over the past few years. The mobile telecommunication network comprises switching functions, service logic functions, database functions, and Mobility Management (MM) functions that enable subscribers to be mobile. These are some of the functions provided by Mobile Switching Centers (MSCs) for serving Circuit Switched (CS) connections, by Visitor Location Registers (VLR) for serving CS connections, or by other network entities, for example, Serving GPRS Support Node (SGSN) for Packet Switched (PS) connections (GPRS refers to General Packet Radio System).

Generally, the database in the Core Network (CN) keeps tracks of the location of Mobile Stations (MSs). In one case, the CN comprises both entities, MSC (or MSC/VLR) and SGSN, to implement such database. Each of the MSs can have a location update service, a CS or PS connection service from the CN by

sending radio signals to its Base Station (BS). Each of the BSs is controlled by a Radio Network Controller (RNC) which connects to the CN.

In the existing mobile telecommunication systems, e.g. the 2nd generation mobile telecommunication systems, the Core Network (CN) only has MSC/VLR CN entity for serving Circuit Switched (CS) connections, and the CN configuration is simply a CN with MSC/VLR CN entities. Accordingly, the Mobile Station (MS) knows the configuration of the CN as well as the type of services subscribed to a user, i.e. CS connection service. Further, a registration procedure, such as a location update by the MS can also be readily done.

However, more and more mobile telecommunication systems are developed to have different kinds of CN configurations and different types of CN entities, e.g. a 3rd generation mobile telecommunication system. The CN of the 3rd generation mobile telecommunication system may include a variety of CN entities, such as SGSN CN entity, MSC/VLR CN entity, etc. Further, the CN may have a separate MSC/VLR CN entity and SGSN CN entity configuration, a separate but connected by Gs interface MSC/VLR CN entity and SGSN CN entity configuration, an integrated MSC/SGSN CN entity configuration. Accordingly, a Mobile Station (MS) does not necessarily know which services are subscribed to a user. For example, in Global System for Mobile communications (GSM), this information is held in the Home Location Register (HLR). Thus, the MS does not know where to perform a registration procedure, such as location update, or which type of service is desired by the user, e.g. CS or PS attach/detach service, or other Mobility Management (MM) procedures.

Accordingly, there is a need for a solution to providing MM procedures of a Mobile Station (MS) in a Core Network (CN) of a mobile telecommunication system regardless of the CN configuration and regardless of the types of CN entities in the CN.

SUMMARY OF THE INVENTION

To overcome the limitations or problems in the prior art described above, and to overcome other limitations that will become apparent upon reading and understanding the present specification, the present invention provides a method, a system, and article of manufacture for providing Mobility Management (MM) procedure of a Mobile Station (MS) in a Core Network (CN) of a mobile telecommunication system.

The present invention solves the above-described problems by providing an indicator in Mobility Management (MM) procedures, e.g. location update, or attach/detach procedure, to specify the procedure type executed in the Core Network (CN) entities.

5 When a Mobile Station (MS) executes location update, detach, or attach MM procedure (hereafter referred to as update procedure), there is an indicator in a Mobility Management (MM) message, which describes the update type, e.g. for all entities (including MSC/VLR CN entity and SGSN CN entity, etc.), for MSC/VLR CN entity only, or for SGSN CN entity only, etc. Accordingly, the MS updates all
10 possible CN entities when the indicator the update type is for all entities, the MS only updates MSC/VLR CN entity when the indicator of the update type is for MSC/VLR CN entity only, and the MS only updates SGSN CN entity when the indicator of the update type is for SGSN CN entity only. This indicator is sent with the MM message, which requests the update from the CN, e.g. location update
15 request, attach request and detach request message, etc.

 The CN entity next updates the HLR (Home Location Register) and then sends an acknowledgment message back to the MS (in case of a detach procedure, the CN entity may not send an acknowledgment back to the MS). The CN entity indicates in the acknowledgment message the entities that were updated. The CN
20 entity also indicates in the acknowledgment message the entities that still are to be updated. There are many different options to perform the update because of the different types of CN entities and different CN configurations. The CN receives this information from the Home Location Register (HLR) where information of the services that MS has subscribed is stored.

25 In one embodiment of the present invention, there is a method for providing a mobility management procedure of a Mobile Station (MS) in a Core Network (CN) of a mobile telecommunication system, the CN including a plurality of CN entities, comprising:

- 30 a) determining, by the MS, to which of the CN entities to perform the update procedure;
- b) updating, by the MS, the CN entity;
- c) acknowledging the MS, by the CN, whether update is successful or failed; and

d) acknowledging the MS, by the CN, whether update of other CN entity is needed, if needed, defining, by the CN, to which of other CN entity to perform update, and continuing b)–d).

5 In one aspect of the present invention, the MS has an indicator which defines an update type. The update type includes one of: all CN entities; one type of CN entity only, such that if the indicator has the update type of all CN entities, the MS updates the all CN entities; and if the indicator has the update type of one type of CN entity only, the MS updates the one type of CN entity only.

10 In another aspect of the invention, the plurality of the CN entities include a SGSN (Serving GPRS Support Node) CN entity, a MSC/VLR (Mobile Switching Center/Visitor Location Register) CN entity, such that if the indicator has the update type of all CN entities, the MS updates the all CN entities including all of the SGSN CN entity and the MSC/VLR CN entity; if the indicator has the update type of SGSN CN entity only, the MS updates the SGSN CN entity only; if the indicator has the
15 update type of MSC/VLR CN entity only, the MS updates the MSC/VLR CN entity only.

In one embodiment of the invention, the CN is a CN with separate MSC/VLR CN entity and SGSN CN entity. If the indicator has the update type of all entities, the MS registers the MSC/VLR CN entity, the CN acknowledges that the
20 update of the MSC/VLR CN entity is successful and that update of SGSN CN entity is needed. Upon receipt of the acknowledgment from the CN that update of SGSN CN entity is needed, the MS registers the SGNS CN entity, the CN acknowledges that the update of the SGSN CN entity is successful and that no update of other entity is needed.

25 Further in one embodiment of the present invention wherein the CN is a CN with separate MSC/VLR CN entity and SGSN CN entity, if the indicator has the update type of all entities, the MS registers the SGSN CN entity, the CN acknowledges that the update of the SGSN CN entity is successful and that update of MSC/VLR CN entity is needed. Upon receipt of the acknowledgment from the CN
30 that update of MSC/VLR CN entity is needed, the MS registers the MSC/VLR CN entity, the CN acknowledges that the update of the MSC/VLR CN entity is successful and that no update of other entity is needed.

Still in one embodiment of the present invention wherein the CN is a CN with separate MSC/VLR CN entity and SGSN CN entity, if the indicator has the
35 update type of MSC/VLR CN entity only, the MS registers the MSC/VLR CN entity,

the CN acknowledges that the update of the MSC/VLR CN entity is successful and that no update of other CN entity is needed.

Yet in one embodiment of the present invention wherein the CN is a CN with separate MSC/VLR CN entity and SGSN CN entity, if the indicator has the update
5 type of SGSN CN entity only, the MS registers the SGSN CN entity, the CN acknowledges that the update of the SGSN CN entity is successful and that no update of other CN entity is needed.

In another embodiment of the present invention, the CN is a CN with separate but connected by Gs interface MSC/VLR CN entity and SGSN CN entity.
10 If the indicator has the update type of all entities, the MS registers the MSC/VLR CN entity first and then registers the SGSN CN entity via the Gs interface, the CN acknowledges that the update of the MSC/VLR CN entity and the SGSN CN entity is successful and that no update of other entity is needed.

Alternatively, in another embodiment of the invention, the CN is a CN with separate but connected by Gs interface MSC/VLR CN entity and SGSN CN entity.
15 If the indicator has the update type of all entities, the MS registers the SGSN CN entity first and then registers the MSC/VLR CN entity via the Gs interface, the CN acknowledges that the update of the SGSN CN entity and the MSC/VLR CN entity is successful and that no update of other entity is needed.

Further in another embodiment of the invention wherein the CN is a CN with separate but connected by Gs interface MSC/VLR CN entity and SGSN CN entity, if the indicator has the update type of MSC/VLR CN entity only, the MS registers the MSC/VLR CN entity, the CN acknowledges that the update of the MSC/VLR CN
20 entity is successful and that no update of other entity is needed.

Still in another embodiment of the invention wherein the CN is a CN with separate but connected by Gs interface MSC/VLR CN entity and SGSN CN entity, if the indicator has the update type of SGSN CN entity only, the MS registers the SGSN CN entity, the CN acknowledges that the update of the SGSN CN entity is
25 successful and that no update of other entity is needed.

In an alternative embodiment of the invention, the CN is a CN with integrated MSC/SGSN CN entity. If the indicator has the update type of all entities, the MS registers the MSC/SGSN CN entity, the CN acknowledges that the update of the MSC/SGSN CN entity is successful and that no update of other entity is needed.
30

Further in an alternative embodiment of the invention wherein the CN is a
35 CN with integrated MSC/SGSN CN entity, if the indicator has the update type of

MSC/VLR CN entity only, the MS registers the MSC CN entity, the CN acknowledges that the update of the MSC CN entity is successful and that no update of other entity is needed.

5 Still in an alternative embodiment of the invention wherein the CN is a CN with integrated MSC/SGSN CN entity, if the indicator has the update type of SGSN CN entity only, the MS registers the SGSN CN entity, the CN acknowledges that the update of the SGSN CN entity is successful and that no update of other entity is needed.

10 Another aspect of the invention is that the update includes location update, a circuit switch attach/detach, or a packet switch attach/detach.

The present invention also provides a system of providing an update procedure in a mobile telecommunication system. In one embodiment, the system includes:

15 a Core Network (CN), the CN including a plurality of CN entities;
a Mobile Station (MS), the MS determining to which of the CN entities to perform the update procedure and updating the CN entity; and

20 wherein after update of the CN entity, the CN acknowledging the MS whether update is successful or failed, and whether update of other CN entity is needed, if needed, the CN defining to which of other CN entity to perform update and continuing update of the other CN entity.

One advantage of the present invention is that it provides means for handling different kinds of CN configurations or architectures when MS is executing MM procedures in a mobile communication network system

25 These and various other advantages and features of novelty which characterize the invention are pointed out with particularity in the claims annexed hereto and form a part hereof. However, for a better understanding of the invention, its advantages, and the objects obtained by its use, reference should be made to the drawings which form a further part hereof, and to accompanying descriptive matter, in which there are illustrated and described specific examples of an apparatus in accordance with the
30 invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Referring now to the drawings in which like reference numbers represent corresponding parts throughout:

Fig. 1 illustrates an update procedure of a Mobile Station (MS) in a first Core Network (CN) of a mobile telecommunication system in accordance with the present invention;

Fig. 2 illustrates an update procedure of a Mobile Station (MS) in a second Core Network (CN) of a mobile telecommunication system in accordance with the present invention;

Fig. 3 illustrates an update procedure of a Mobile Station (MS) in a third Core Network (CN) of a mobile telecommunication system in accordance with the present invention;

Fig. 4 illustrates a flow chart of an update procedure of a Mobile Station (MS) adapted for different types of Core Network (CN) configurations in accordance with the present invention;

Fig. 5 illustrates one type of update procedure, i.e. a location update, of a Mobile Station (MS) in the first Core Network (CN) with separate CN entities in accordance with the present invention;

Fig. 6 illustrates one type of update procedure, i.e. a location update, of a Mobile Station (MS) in the second Core Network (CN) with separate CN entities having interface Gs in accordance with the present invention;

Fig. 7 illustrates one type of update procedure, i.e. a location update, of a Mobile Station (MS) in the third Core Network (CN) with integrated CN entities in accordance with the present invention;

Fig. 8 illustrates an alternative embodiment of one type of update procedure, i.e. a location update, of a Mobile Station (MS) in the first Core Network (CN) with separate CN entities as shown in Fig. 5; and

Fig. 9 illustrates another alternative embodiment of one type of update procedure, i.e. a location update, of a Mobile Station (MS) in the first Core Network (CN) with separate CN entities as shown in Fig. 5.

DETAILED DESCRIPTION OF THE INVENTION

This invention relates in general to a mobile cellular communication system, more particularly to a mobile cellular communication system used in 2nd and 3rd generation mobile cellular system, and more still particularly to an indicator in mobility management (MM) procedures to specify a procedure type executed in Core Network (CN) entities.

In the following description of the exemplary embodiment, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration the specific embodiment in which the invention may be practiced. It is to be understood that other embodiments may be utilized as structural changes may be made without departing from the scope of the present invention.

The foregoing description of the exemplary embodiment of the invention has been presented for the purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed. Many modifications and variations are possible in light of the above teaching. It is intended that the scope of the invention be limited not with this detailed description, but rather by the claims appended hereto.

In Figs. 1–3, three exemplary Core Network (CN) configurations are shown. It is appreciated that other CN configurations can be used without departure from the principles of the present invention.

In Fig. 1, a CN 20 has a CN entity MSC/VLR 22 and a CN entity SGSN 24. The MSC/VLR 22 and SGSN 24 are separate from each other in the CN 20. A Mobile Station (MS) 26 sends a Location Area (LA) update request, LA_UPDATE_REQ as shown in Figs. 5–7, to the CN 20. There is an indicator in a Mobility Management (MM) message which describes an update type, e.g. updating all CN entities, MSC/VLR CN entities only, or SGSN CN entities only. As an example, Table 1 shows different update types. When the type in the indicator is for all entities (i.e. type = 0), all CN entities including MSC/VLR CN entity and SGSN CN entity are to be updated. When the type in the indicator is for MSC/VLR CN entity only (i.e. type = 1), only the MSC/VLR CN entity is updated. Similarly, when the type in the indicator is for SGSN CN entity only (i.e. type = 2), only the SGSN CN entity is updated.

Table 1. Update type indicator

Indicator	Update type
0	All entities (e.g. MSC/VLR and SGSN)
1	MSC/VLR entity only
2	SGSN entity only

It is appreciated that other CN entities can be used within the scope of the present invention. For example, the update type can be for MSC/VLR CN entity and another CN entity only, or SGSN CN entity and another CN entity only.

The corresponding CN entity MSC/VLR 22 or SGSN 24 sends an acknowledgment message to the MS 26. The CN entity indicates in the acknowledgment message the entity that has been updated. The CN entity also indicates in the acknowledgment message the entity that is still to be updated. As an example, the following Table 2 shows several options to further update entity.

Table 2. Update acknowledgment indicator

Indicator	Updated services	Possible to update
0	MSC/VLR	SGSN
1	MSC/VLR	No other entity possible
2	SGSN	MSC/VLR
3	SGSN	No other entity possible
4	MSC/VLR and SGSN	No other entity possible
5	None	SGSN
6	None	MSC/VLR
7	None	No other entity possible

When the MSC/VLR CN entity has been updated and acknowledges that the SGSN CN entity is still to be updated (type = 0), the SGSN CN entity will be updated by the MS next. When the MSC/VLR CN entity has been updated and acknowledges that no update is needed (type = 1), the update procedure is complete. When the SGSN CN entity has been updated and acknowledges that the MSC/VLR CN entity is still to be updated (type = 2), the MSC/VLR CN entity will be updated by the MS next. When the SGSN CN entity has been updated and acknowledges that no update is needed (type = 3), the update procedure is complete. When the MSC/VLR CN entity and SGSN CN entity have been updated and acknowledge that no update is needed (type = 4), the update procedure is complete. When none of the entity has been updated (type = 5), it is a default to indicate that no update is needed,

and the update procedure is complete. It is appreciated that many other different options can be performed within the scope and spirit of the present invention.

Further in Fig. 1, a Radio Network Controller 28 is used between the MS 26 and the CN 20. Further, a Home Location Register (HLR) 29 holds information of which service (or entity) is subscribed to a user. Once an update request is made by the MS 26 to a CN entity, the CN entity updates the HLR 29. The HLR 29 next acknowledges the CN entity whether update is successful or failed and whether update of other CN entity is needed. Then, the CN entity acknowledges the RNC 28 or the MS 26 through the RNC 28 whether update is successful or failed and whether update of other CN entity is needed. If needed, the update of the defined CN entity continues.

In Fig. 2, exemplary CN 30 has a CN entity MSC/VLR 32 and a CN entity SGSN 34. The MSC/VLR 32 and SGSN 34 are separate from each other but connected by an interface Gs. A Mobile Station (MS) 36 sends an update request to the CN 30. Similarly, a RNC 38 is used between the MS 36 and the CN 30. Further, a Home Location Register (HLR) 39 holds information of which service (or entity) is subscribed to a user. Once an update request is made by the MS 36, the CN entity updates the HLR 39. The HLR 39 next acknowledges the CN entity whether update is successful or failed and whether update of other CN entity is needed. If needed, an update request is made by the CN entity to the other CN entity, the other CN entity updates the HLR 39. The HLR 39 next acknowledges the other CN entity whether update is successful or failed and whether update of another CN entity is needed. If needed, the update continues. When there is no update is needed, the CN entity acknowledges the RNC 38 or the MS 36 through the RNC 38 whether update is successful or failed.

In Fig. 3, an exemplary CN 40 has a CN entity MSC/VLR 42 and a CN entity SGSN 44. The MSC/VLR 42 and SGSN 44 are integrated to each other in the CN 40. A Mobile Station (MS) 46 sends an update request to the CN 40. A RNC 48 is used between the MS 46 and the CN 40. Further, a Home Location Register (HLR) 49 holds information of which service (entity) is subscribed to a user. Once an update request is made by the MS 46, the CN entity updates the HLR 49. The HLR 49 next acknowledges the CN entity whether update is successful or failed. The CN entity acknowledges the RNC 48 or the MS 46 through the RNC 48 whether update is successful or failed

In the following exemplary cases, there are presented options how the MS may base the decision of the update type into different grounds and how the CN entity behaves in these cases:

1. MS may always try to update to all CN entities or services (e.g. see
5 *Table 1.*, update type = 0). The CN entity sends an acknowledgment to the MS to inform the MS to which CN entity the update was successful. It is up to the MS to proceed the updating procedure to correct new CN entities if this is needed. Accordingly, the CN configuration is informed to the MS when the MS receives the acknowledgment message from the CN entity. Alternatively, the MS can obtain the
10 CN configuration information from a Common Control Channel, e.g. a Broadcast Control Channel (BCCH) in GSM. Accordingly, when the MS has no knowledge of the CN configuration., the MS can try "dummily," and the CN may deny the update if the update is not possible to be performed in the CN.
2. Same as option 1 except that now the MS tries to update to some (it is
15 up to the MS to decide which CN entity) CN entities (or services). The CN entity sends an acknowledgment message to the MS to inform the MS to which entity the update was successful. It is up to the MS to proceed the updating procedure to correct the new entities if this is needed.
3. The MS may always try to update all CN entities or services (e.g. see
20 *Table 1.*, update type = 0). The CN entity sends an acknowledgment message to the MS to inform the MS to which CN entity the update was successful and to which CN entity the update may/must also be made (e.g. see *Table 2.*, update acknowledgment type = 0). It is noted that if the CN (e.g. public land mobile network = PLMN in GSM) does not have CN entities or the services, the CN may
25 remove those CN entities or the services from the "must/may update list," or the MS may remove those CN entities if the MS knows the CN configuration. Alternatively, the MS can obtain the CN configuration information if the CN configuration is broadcast in a Common Control Channel, e.g. Broadcast Control Channel (BCCH) used in GSM.
- 30 4. Same as the option 3 except that now the MS tries to update to some (up to the MS to decide which CN entities) CN entities or services. The CN entity informs the MS to which entity the update was successful and to which CN entity the update may/must also be made.

5. MS may first analyze the CN configuration from information broadcast in a Common Control Channel, e.g. Broadcast Control Channel (BCCH), and then send the update/updates to the propriety CN entity/entities based on the ability of the MS, or the "willingness" of the subscriber, etc. The CN may inform in the acknowledgment message to which CN entity the MS is also able to perform update (i.e. similar to those shown in *Table 2*).

Fig. 4 shows a flow chart of an update procedure of a Mobile Station (MS) adapted for different types of Core Network (CN) configurations in accordance with the present invention. It is appreciated that the flow chart is only for illustration, not for limitation, and that the steps and sequences may be varied within the principles of the present invention. The operation starts in box 50. In box 52, MS determines to which CN entity to perform the update, e.g. all CN entities, or MSC/VLR CN entity only, or SGSN CN entity only, etc. Then, in box 54, the MS updates the determined CN entity/entities. Next, in box 56, the CN entity acknowledges the update success or fail. The CN entity also acknowledges whether additional update of CN entity/entities is needed in box 58. If no, the operation ends in box 60. If additional update to the CN entity/entities is needed, the CN entity informs the MS to which other CN entity to perform further update in box 62. Then, the operation continues in box 54.

Figs. 5,6,7 illustrate one of the update procedure, i.e. the location update procedure adapted for three different CN configurations. The three examples are described in the above discussed option 3. Fig. 5 shows a location update executed in a CN configuration with separate MSC/VLR CN entity and SGSN CN entity. Fig. 6 shows a location update executed in a CN configuration with separate but connected by Gs MSC/VLR CN entity and SGSN CN entity. Fig. 7 shows a location update executed in a CN configuration with integrated MSC/VLR CN entity and SGSN CN entity.

Location update procedure to both separate MSC/VLR and SGSN entities

As shown in Fig. 5, a MS requests to attach to the CN for all possible services, e.g. both Circuit Switched (CS) and Packet Switched (PS) services offered by MSC/VLR and SGSN CN entities, respectively. The MS sends a location update message with an indicator indicating that this update is for all entities (or services). The location update message may be forwarded first to a default CN entity (e.g. a SGSN CN entity or a MSC/VLR CN entity), which updates location to a HLR. The

HLR then sends subscriber data from the HLR to the CN entity, and the HLR also informs the CN entity the other services that are possible for the MS to update. The CN then sends an acknowledgment message with an indicator describing the update type that was executed successfully in the CN (e.g. SGSN CN entity has been
5 updated and MSC/VLR CN entity is possible to update). Accordingly, in case the update type does not match with the required procedure (e.g. MS requests a SGSN CN entity, but there is no SGSN CN entity in the CN), then the MS continues with an appropriate MM message to finish the update (e.g. there is a MSC/VLR CN entity in the CN).

10 Accordingly, Fig. 5 illustrates the following exemplary sequence of the operation:

1. The MS sends a Location Area (LA) update to the CN. The MS indicates that it wants to perform a LA update for both CS and PS services (i.e. update type = 0 (see *Table 1*)).
- 15 2. The SGSN updates the location of the MS to the HLR.
3. The HLR acknowledges the update.
4. The SGSN then indicates to the MS that the LA update of the SGSN (or for PS service) was successful, and that the user has also subscribed MSC/VLR (or CS service), i.e. update acknowledgment type = 2, see *Table 2*).
- 20 5. Based on the LA update acknowledgment sent by the SGSN, the MS sends a LA update that is routed to the MSC/VLR by the RNC, i.e. update type = 1 (see *Table 1*).
6. The MSC/VLR updates the location of the MS to the HLR.
7. The HLR acknowledges the update.
- 25 8. The MSC/VLR then indicates to the MS that the LA update was successful for the MSC (or for CS services), i.e. update acknowledgment type = 3 (see *Table 2*).

It is appreciated that the steps or sequence of the above operation can be varied within the principles of the present invention.

Location update procedure to both separate MSC/VLR and SGSN
entities connected by Gs interface

As shown in Fig. 6, the MS performs a location update message when the MS makes an attach to the CN, or the MS enters a new Location Area (LA) while the MS has both SGSN and MSC/VLR attached and in the idle state.

1. The MS sends an update to the CN. The MS indicates that it requests to perform a Location Area update (LA) update for both CS and PS services, i.e. update type = 0 (see Table 1).
2. If LA update is an inter-SGSN update, then the HLR is informed.
- 10 3. The HLR sends acknowledgment back to the SGSN.
4. The SGSN sends the LA update to the MSC/VLR via a network Gs interface.
5. If the LA update is an inter-MSC/VLR update, then the HLR is informed.
- 15 6. The HLR sends acknowledgment back to the MSC/VLR.
7. The MSC/VLR sends acknowledgment back to the SGSN.
8. The SGSN sends to the MS an update accept message which indicates that both CS and PS service update was successful, i.e. update acknowledgment type = 4 (see Table 2).
- 20 It is appreciated that the steps or sequence of the above operation can be varied within the principles of the present invention.

Location update procedure to Integrated MSC/SGSN entity

Fig. 7 illustrates the following exemplary sequence of the operation in the CN configuration having integrated MSC/SGSN CN entity:

- 25 1. The MS sends an update to the CN. The MS indicates that it requests to perform a LA update for both CS and PS services, i.e. update type = 0 (see Table 1).

2. If the LA update is inter-Integrated MSC/SGSN update, then the HLR is informed.
3. The HLR sends acknowledgment back to the Integrated MSC/SGSN.
4. The Integrated MSC/SGSN sends to the MS an update accept message which indicates that both CS and PS service update was successful, i.e. update acknowledgment type = 4 (see *Table 2*).

It is appreciated that the steps or sequence of the above operation can be varied within the principles of the present invention. The above examples illustrate that all entities are requested to be updated (update type = 0 in *Table 1*). It is appreciated that other update type, i.e. type = 1, 2, etc. can be illustrated within the scope of the present invention. Accordingly, the present invention enables means for handling different kinds of CN architectures or configurations when MS is executing MM procedures in a mobile network system.

It is appreciated that other embodiments of location update procedure as described above can be used with modification within the scope and principles of the present invention. For example, besides MS, any other network elements, such as RNC or CN entity, etc., can be arranged, configured, or implemented to have an indicator to determine to which CN entity to perform the location update. It is also appreciated that besides MS, any other network elements, such as RNC or CN entity, etc. can be used to update the CN entity or other CN entity, respectively. Further, it is appreciated that besides CN entity, any other network element, such as RNC, etc., can be used to acknowledge whether update is successful or failed and also define to which CN entity to perform further update.

Within many modified embodiments in accordance with the principles of the invention, examples are shown in Figs. 8 and 9. In Fig. 8, the operation of the location update procedure is similar to that of shown in Fig. 5, except that the SGSN indicates to the RNC, instead of the MS, that the LA update of the SGSN was successful or failed (see step 4 in Fig. 8) and that the user has also subscribed MSC/VLR; and except that the RNC, instead of the MS, sends a LA update to the MSC/VLR (see step 5 in Fig. 8). In Fig. 9, the operation of the location update procedure is similar to that of shown in Fig. 5, except that the MS sends a Location Area (LA) update to the RNC (see step 1 in Fig. 9). If the MS indicates that both CS and PS services should be updated, then the RNC sends LA update to both the

SGSN and the MSC/VLR (see step 2 in Fig. 9), and the SGSN and the MSC/VLR update the HLR, respectively, and then acknowledge the RNC (see steps 5 and 8 in Fig. 9) which in turn acknowledges the MS (see step 9 in Fig. 9).

5 It is also appreciated that the Circuit Switch (CS) or Packet Switch (PS) attach/detach Mobility Management (MM) procedures can be implemented in a similar manner without departure from the spirit or scope of the present invention.

The foregoing description of the exemplary embodiment of the invention has been presented for the purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed. Many
10 modifications and variations are possible in light of the above teaching. It is intended that the scope of the invention be limited not with this detailed description, but rather by the claims appended hereto.

WHAT IS CLAIMED IS:

1. A method for providing a mobility management procedure of a Mobile Station (MS) in a Core Network (CN) of a mobile telecommunication system, the
5 CN including a plurality of CN entities, comprising:
 - a) determining, by the MS, to which of the CN entities to perform the update procedure;
 - b) updating, by the MS, the determined CN entity;
 - c) acknowledging the MS, by the determined CN entity, whether update
10 is successful or failed; and
 - d) acknowledging the MS, by the determined CN entity, whether update of other CN entity is needed, if needed, defining, by the determined CN entity, to which of other CN entity to perform update, and continuing b)–d).
- 15 2. The method of claim 1, wherein the MS has a indicator which defines an update type, the update type including one of: all CN entities; one type of CN entity only, such that if the indicator has the update type of all CN entities, the MS updates the all CN entities; and if the indicator has the update type of one type of CN entity only, the MS updates the one type of CN entity only.
- 20 3. The method of claim 1, wherein the plurality of the CN entities include a SGSN (Serving GPRS Support Node) CN entity, a MSC/VLR (Mobile Switching Center/Visitor Location Register) CN entity.
- 25 4. The method of claim 2, wherein the plurality of the CN entities include a SGSN (Serving GPRS Support Node) CN entity, a MSC/VLR (Mobile Switching Center/Visitor Location Register) CN entity, such that if the indicator has the update type of all CN entities, the MS updates the all CN entities including all of the SGSN CN entity and the MSC/VLR CN entity; if the indicator has the update type of SGSN CN entity only, the MS updates the SGSN CN entity only; if the indicator has the update type of MSC/VLR CN entity only, the MS updates the MSC/VLR CN entity only.
- 30 5. The method of claim 4, wherein the CN is a CN with separate MSC/VLR CN entity and SGSN CN entity.

6. The method of claim 4, wherein the CN is a CN with separate MSC/VLR CN entity and SGSN CN entity, wherein if the indicator has the update type of all entities, the MS registers the MSC/VLR CN entity, the CN acknowledges that the update of the MSC/VLR CN entity is successful and that update of SGSN CN entity is needed.
7. The method of claim 6, wherein upon receipt of the acknowledgment from the CN that update of SGSN CN entity is needed, the MS registers the SGSN CN entity, the CN acknowledges that the update of the SGSN CN entity is successful and that no update of other entity is needed.
8. The method of claim 4, wherein the CN is a CN with separate MSC/VLR CN entity and SGSN CN entity, wherein if the indicator has the update type of all entities, the MS registers the SGSN CN entity, the CN acknowledges that the update of the SGSN CN entity is successful and that update of MSC/VLR CN entity is needed.
9. The method of claim 8, wherein upon receipt of the acknowledgment from the CN that update of MSC/VLR CN entity is needed, the MS registers the MSC/VLR CN entity, the CN acknowledges that the update of the MSC/VLR CN entity is successful and that no update of other entity is needed.
10. The method of claim 4, wherein the CN is a CN with separate MSC/VLR CN entity and SGSN CN entity, wherein if the indicator has the update type of MSC/VLR CN entity only, the MS registers the MSC/VLR CN entity, the CN acknowledges that the update of the MSC/VLR CN entity is successful and that no update of other CN entity is needed.
11. The method of claim 4, wherein the CN is a CN with separate MSC/VLR CN entity and SGSN CN entity, wherein if the indicator has the update type of SGSN CN entity only, the MS registers the SGSN CN entity, the CN acknowledges that the update of the SGSN CN entity is successful and that no update of other CN entity is needed.
12. The method of claim 4, wherein the CN is a CN with separate but connected by Gs interface MSC/VLR CN entity and SGSN CN entity.

13. The method of claim 4, wherein the CN is a CN with separate but connected by Gs interface MSC/VLR CN entity and SGSN CN entity, wherein if the indicator has the update type of all entities, the MS registers the MSC/VLR CN entity first and then registers the SGSN CN entity via the Gs interface, the CN acknowledges that
5 the update of the MSC/VLR CN entity and the SGSN CN entity is successful and that no update of other entity is needed.

14. The method of claim 4, wherein the CN is a CN with separate but connected by Gs interface MSC/VLR CN entity and SGSN CN entity, wherein if the indicator has the update type of MSC/VLR CN entity only, the MS registers the MSC/VLR
10 CN entity, the CN acknowledges that the update of the MSC/VLR CN entity is successful and that no update of other entity is needed.

15. The method of claim 4, wherein the CN is a CN with separate but connected by Gs interface MSC/VLR CN entity and SGSN CN entity, wherein if the indicator has the update type of SGSN CN entity only, the MS registers the SGSN CN entity,
15 the CN acknowledges that the update of the SGSN CN entity is successful and that no update of other entity is needed.

16. The method of claim 4, wherein the CN is a CN with integrated MSC/SGSN CN entity.

17. The method of claim 4, wherein the CN is a CN with integrated MSC/SGSN
20 CN entity, wherein if the indicator has the update type of all entities, the MS registers the MSC/SGSN CN entity, the CN acknowledges that the update of the MSC/SGSN CN entity is successful and that no update of other entity is needed.

18. The method of claim 4, wherein the CN is a CN with integrated MSC/SGSN CN entity, wherein if the indicator has the update type of MSC/VLR CN entity only,
25 the MS registers the MSC CN entity, the CN acknowledges that the update of the MSC CN entity is successful and that no update of other entity is needed.

19. The method of claim 4, wherein the CN is a CN with integrated MSC/SGSN CN entity, wherein if the indicator has the update type of SGSN CN entity only, the MS registers the SGSN CN entity, the CN acknowledges that the update of the
30 SGSN CN entity is successful and that no update of other entity is needed.

20. The method of claim 1, wherein the update includes location update.
21. The method of claim 1, wherein the update includes a circuit switch attach/detach.
22. The method of claim 1, wherein the update includes a packet switch
5 attach/detach.
23. A system of providing an update procedure in a mobile telecommunication system, comprising:
a Core Network (CN), the CN including a plurality of CN entities;
a Mobile Station (MS), the MS determining to which of the CN entities to
10 perform the update procedure and updating the determined CN entity; and
wherein after update of the determined CN entity, the determined CN entity acknowledging the MS whether update is successful or failed, and whether update of other CN entity is needed, if needed, the CN defining to which of other CN entity to perform update and continuing update of the other CN entity.
- 15 24. The system of claim 23, wherein the MS has an indicator which defines an update type, the update type including one of: all CN entities; one type of CN entity only, such that if the indicator has the update type of all CN entities, the MS updates the all CN entities; and if the indicator has the update type of one type of CN entity only, the MS updates the one type of CN entity only.
- 20 25. The system of claim 23, wherein the plurality of the CN entities include a SGSN (Serving GPRS Support Node) CN entity, a MSC/VLR (Mobile Switching Center/Visitor Location Register) CN entity.
26. The system of claim 24, wherein the plurality of the CN entities include a SGSN (Serving GPRS Support Node) CN entity, a MSC/VLR (Mobile Switching
25 Center/Visitor Location Register) CN entity, such that if the indicator has the update type of all CN entities, the MS updates the all CN entities including all of the SGSN CN entity and the MSC/VLR CN entity; if the indicator has the update type of SGSN CN entity only, the MS updates the SGSN CN entity only; if the indicator has the update type of MSC/VLR CN entity only, the MS updates the MSC/VLR CN entity
30 only.

27. The system of claim 26, wherein the CN is a CN with separate MSC/VLR CN entity and SGSN CN entity.
28. The system of claim 26, wherein the CN is a CN with separate MSC/VLR CN entity and SGSN CN entity, wherein if the indicator has the update type of all
5 entities, the MS registers the MSC/VLR CN entity, the CN acknowledges that the update of the MSC/VLR CN entity is successful and that update of SGSN CN entity is needed.
29. The system of claim 28, wherein upon receipt of the acknowledgment from the CN that update of SGSN CN entity is needed, the MS registers the SGNS CN
10 entity, the CN acknowledges that the update of the SGSN CN entity is successful and that no update of other entity is needed.
30. The system of claim 26, wherein the CN is a CN with separate MSC/VLR CN entity and SGSN CN entity, wherein if the indicator has the update type of all
15 entities, the MS registers the SGSN CN entity, the CN acknowledges that the update of the SGSN CN entity is successful and that update of MSC/VLR CN entity is needed.
31. The system of claim 30, wherein upon receipt of the acknowledgment from the CN that update of MSC/VLR CN entity is needed, the MS registers the
20 MSC/VLR CN entity, the CN acknowledges that the update of the MSC/VLR CN entity is successful and that no update of other entity is needed.
32. The system of claim 26, wherein the CN is a CN with separate MSC/VLR CN entity and SGSN CN entity, wherein if the indicator has the update type of
25 MSC/VLR CN entity only, the MS registers the MSC/VLR CN entity, the CN acknowledges that the update of the MSC/VLR CN entity is successful and that no update of other CN entity is needed.
33. The system of claim 26, wherein the CN is a CN with separate MSC/VLR CN entity and SGSN CN entity, wherein if the indicator has the update type of
30 SGSN CN entity only, the MS registers the SGSN CN entity, the CN acknowledges that the update of the SGSN CN entity is successful and that no update of other CN entity is needed.

34. The system of claim 26, wherein the CN is a CN with separate but connected by Gs interface MSC/VLR CN entity and SGSN CN entity.

35. The system of claim 26, wherein the CN is a CN with separate but connected by Gs interface MSC/VLR CN entity and SGSN CN entity, wherein if the indicator
5 has the update type of all entities, the MS registers the MSC/VLR CN entity first and then registers the SGSN CN entity via the Gs interface, the CN acknowledges that the update of the MSC/VLR CN entity and the SGSN CN entity is successful and that no update of other entity is needed.

36. The system of claim 26, wherein the CN is a CN with separate but connected
10 by Gs interface MSC/VLR CN entity and SGSN CN entity, wherein if the indicator has the update type of MSC/VLR CN entity only, the MS registers the MSC/VLR CN entity, the CN acknowledges that the update of the MSC/VLR CN entity is successful and that no update of other entity is needed.

37. The system of claim 26, wherein the CN is a CN with separate but connected
15 by Gs interface MSC/VLR CN entity and SGSN CN entity, wherein if the indicator has the update type of SGSN CN entity only, the MS registers the SGSN CN entity, the CN acknowledges that the update of the SGSN CN entity is successful and that no update of other entity is needed.

38. The system of claim 26, wherein the CN is a CN with integrated MSC/SGSN
20 CN entity.

39. The system of claim 26, wherein the CN is a CN with integrated MSC/SGSN CN entity, wherein if the indicator has the update type of all entities, the MS registers the MSC/SGSN CN entity, the CN acknowledges that the update of the MSC/SGSN CN entity is successful and that no update of other entity is needed.

25 40. The system of claim 26, wherein the CN is a CN with integrated MSC/SGSN CN entity, wherein if the indicator has the update type of MSC/VLR CN entity only, the MS registers the MSC CN entity, the CN acknowledges that the update of the MSC CN entity is successful and that no update of other entity is needed.

41. The system of claim 26, wherein the CN is a CN with integrated MSC/SGSN CN entity, wherein if the indicator has the update type of SGSN CN entity only, the MS registers the SGSN CN entity, the CN acknowledges that the update of the SGSN CN entity is successful and that no update of other entity is needed.
- 5 42. The system of claim 23, wherein the update includes location update.
43. The system of claim 23, wherein the update includes a circuit switch attach/detach.
44. The system of claim 23, wherein the update includes a packet switch attach/detach.
- 10 45. An article of manufacture for a computer-based data processing system, the article of manufacture comprising a computer readable medium having instructions for causing a computer to perform a method for providing an update procedure of a Mobile Station (MS) in a Core Network (CN) of a mobile telecommunication system, the CN including a plurality of CN entities, comprising:
- 15 a) determining, by the MS, to which of the CN entities to perform the update procedure;
- b) updating, by the MS, the determined CN entity;
- c) acknowledging the MS, by the determined CN entity, whether update is successful or failed; and
- 20 d) acknowledging the MS, by the determined CN entity, whether update of other CN entity is needed, if needed, defining, by the determined CN entity, to which of other CN entity to perform update, and continuing b)-d).
46. A method for providing a Mobility Management (MM) procedure of a Mobile Station (MS) in a Core Network (CN) of a mobile telecommunication system, the CN including a plurality of CN entities, comprising:
- 25 a) determining to which of the CN entities to perform the update procedure;
- b) updating the determined CN entity;
- c) acknowledging whether update is successful or failed; and

d) acknowledging whether update of other CN entity is needed, if needed, defining to which of other CN entity to perform update, and continuing b)–d).

5 47. The method of claim 46, wherein the MS has a indicator which defines an update type, the update type including one of: all CN entities; one type of CN entity only, such that if the indicator has the update type of all CN entities, the MS updates the all CN entities; and if the indicator has the update type of one type of CN entity only, the MS updates the one type of CN entity only.

10 48. The method of claim 46, wherein in a), the MS determines to which of the CN entities to perform the update procedure.

49. The method of claim 46, wherein in a), a Radio Network Controller (RNC) determines to which of the CN entities to perform the update procedure, the RNC is connected between the CN and the MS.

15 50. The method of claim 46, wherein in a), one of the CN entities determines to which of the CN entities to perform the update procedure.

51. The method of claim 46, wherein in b), the MS updates the determined CN entity.

52. The method of claim 46, wherein in b), a Radio Network Controller (RNC) updates the determined CN entity.

20 53. The method of claim 46, wherein in b), one of the CN entities updates the determined CN entity.

54. The method of claim 46, wherein in c), the determined CN entity acknowledges whether update is successful or failed.

25 55. The method of claim 46, wherein in c), a Radio Network Controller (RNC) acknowledges whether update is successful or failed.

56. The method of claim 46, wherein in c), one of the CN entities acknowledges whether update is successful or failed.
57. The method of claim 46, wherein in d), the determined CN entity acknowledges whether update of the other CN entity is needed.
- 5 58. The method of claim 46, wherein in c), a Radio Network Controller (RNC) acknowledges whether update of the other CN entity is needed.
59. The method of claim 46, wherein in c), one of the CN entities acknowledges whether update of the other CN entity is needed.
- 10 60. A system of providing an update procedure in a mobile telecommunication system, comprising:
a Core Network (CN), the CN including a plurality of CN entities;
a Mobile Station (MS);
a Radio Network Controller (RNC), the RNC connecting between the MS
15 and the CN; and
wherein a network element selected from the MS, one of the CN entities, or the RNC determines to which of the CN entities to perform the update procedure and updating the determined CN entity; after update of the determined CN entity, the network element selected from one of the CN entities or the RNC acknowledges
20 whether update is successful or failed, and whether update of other CN entity is needed, if needed, the network element selected from the MS, one of the CN entities, or the RNC defines to which of other CN entity to perform update and continuing update of the other CN entity.
61. The system of claim 60, wherein the network element selected from the MS, one of the CN entities, or the RNC has an indicator which defines an update type, the update type including one of: all CN entities; one type of CN entity only, such that if the indicator has the update type of all CN entities, the MS updates the all CN entities; and if the indicator has the update type of one type of CN entity only, the MS updates the one type of CN entity only.
- 25 62. An article of manufacture for a computer-based data processing system, the article of manufacture comprising a computer readable medium having instructions
- 30

for causing a computer to perform a method for providing an update procedure of a Mobile Station (MS) in a Core Network (CN) of a mobile telecommunication system, the CN including a plurality of CN entities, comprising:

- 5 a) determining to which of the CN entities to perform the update procedure;
- b) updating the determined CN entity;
- c) acknowledging whether update is successful or failed; and
- d) acknowledging whether update of other CN entity is needed, if
10 needed, defining to which of other CN entity to perform update, and continuing b)–
d).

FIG. 1




FIG. 2





FIG. 3



4/9

FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8



9/9

FIG. 9



INTERNATIONAL SEARCH REPORT

International Application No

PCI, US 99/16606

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04Q7/38

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 98 32304 A (NOKIA TELECOMMUNICATIONS OY ;KANGAS ISMO (FI); MUSTAJAERVI JARI (F) 23 July 1998 (1998-07-23) page 2, line 1 - line 19 page 4, line 18 -----	1,23,45, 46,60,62
A	WO 98 23119 A (NOKIA TELECOMMUNICATIONS OY ;HUUSKO SAMI (FI); KARI HANNU H (FI)) 28 May 1998 (1998-05-28) page 2, line 10 - line 21 figure 2 figure 1 -----	1,23,45, 46,60,62

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

4 November 1999

Date of mailing of the international search report

15/11/1999

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

PALENCIA GUTIER., C

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/16606

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9832304 A	23-07-1998	FI 970238 A	21-07-1998
		AU 5665998 A	07-08-1998
		EP 0953270 A	03-11-1999
		ZA 9800408 A	29-07-1998
WO 9823119 A	28-05-1998	FI 964598 A	16-05-1998
		AU 5053098 A	10-06-1998
		EP 0945039 A	29-09-1999